


Overview



- 1. menu button
- 2. - adjust

- 3. + adjust
- 4. power on/off

Models

P9621D

Technical Specifications

Panel	Type	17-inch Active Matrix TFT (thin film transistor)	
	Viewable Image Area (diagonal)	17 in (43.2 cm)	
	Screen Opening (W x H)	13.3 x 10.7 in (34.0 x 27.2 cm)	
	Viewing Angle (typical)*	Up to 160 degrees horizontal/140 degrees vertical (10:1 minimum contrast ratio)	
	Brightness (typical)*	Up to 300 nits (cd/m ²)	
	Contrast Ratio (typical)*	Up to 450:1	
	Response Rate (typical)*	25 ms (typical) (rise + fall)	
	Pixel Pitch	0.264mm	
	Color Depth Support	> 16 million colors	
	Backlight Lamp Life (to half brightness)	40K hours	
	*NOTE: All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.		
	Video Input	Plug and Play	Yes
		Input Signal	One 15-pin miniature D-sub connector
Input Impedance		75 ohms ± 2%	
Sync Input		TTL separate synch	
Video Cable		Attached 15-pin D-sub mini connector	
Video Cable Length		59 in (1.5 m); captive	
Signal Interface/ Performance	Horizontal Frequency	30 to 81 kHz	
	Vertical Frequency	56 to 76 Hz	
	Graphics Controller	Genesis or ST	
	Native Resolution	1280 x 1024 @ 60 Hz (recommended)	
	Maximum Resolution (Digital)	N/A	
	Preset VESA Graphic Modes (non-interlaced)	1280 x 1024 @ 60 Hz and 75 Hz 1024 x 768 @ 60 Hz, 70 Hz, and 75 Hz 800 x 600 @ 60 Hz, 72 Hz, and 75 Hz 640 x 480 @ 60 Hz, 72 Hz, and 75 Hz	
	Maximum Pixel Clock Speed	140 MHz	
	User Programmable Modes	Yes, 15	
	Anti-Glare	Yes	
	Anti-Static	Yes	
	Default Color Temperature	6500 degrees Kelvin	
	On Screen Display (OSD) Controls	Buttons or Switches	Power on/off; 3-button OSD (menu, plus, minus)
		Languages	English, French, German, Spanish, Italian, Dutch
		User Controls	Image Control Positioning

Technical Specifications

		Monitor Management (power saver, sleep)
		Color Temperature (6500k, 9300k, Custom)
		Brightness
		Contrast
		Clock, Clock Phase
		Factory Reset
Power	Input Power	100 ~ 240 VAC
	Nominal Current	1.5 A maximum
	Frequency	50 ~ 60 Hz
	Typical Power Consumption	28.5 watts
	Maximum	< 40 watts
	Power Saving	< 2 watts
	Power Cable Length	70.9 in (1.8 m); non-captive
Mechanical	Dimensions (H x W x D)	Unpacked with stand 14.9 x 15.9 x 7.4 in (37.9 x 40.5 x 19.0 cm)
		Unpacked without stand 14.9 x 13.7 x 2.6 in (37.9 x 34.8 x 6.5 cm)
		Packaged 6.8 x 17.8 x 17.8 in (17.5 x 45.4 x 45.4 cm)
	Weight	Unpacked 13.2 lb (6.0 kg)
		Packaged 17.6 lb (8.0 kg)
	Tilt Range	-5 to +30 degrees vertical tilt
	Swivel Range	None
	Height Adjustable	No
	Pivot Rotation	No
	Base	Detachable
Environmental	Temperature – Operating	50° to 95° F (10° to 35° C) non-condensing
	Temperature – Non-operating	-4° to 140° F (-20° to 60° C)
	Humidity – Operating	20% to 80% non-condensing
	Humidity – Non-operating	5% to 90%
	Altitude – Operating	0 to 12,000 ft (0 to 3,658 m)
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,100 m)
Other	Accessories Included	Attached VGA Cable, AC Power Cord
	User Guide Languages	English, French, German, Spanish, Italian, Dutch
	Warranty Languages	English, French, German, Spanish, Italian, Dutch
	Color	Carbonite/Silver
	VESA Mounting	100 mm x 100 mm screw-mounting option; pedestal is attached
	VESA External Mounting	Yes (Standard 4 hole pattern, 100mm)
	Kensington Lock-ready	Yes

Technical Specifications

Certification and Compliance	ISO 9241-3,7,8 VDT guidelines, ISO 13406-2 pixel defect guidelines, MPR-II, CISPR, VCCI, C-UL or CSA (Canada), ACA (Australia), TUV and GS Mark (German ergonomic), BSMI (Taiwan), CCC (China), MIC (South Korea), NOM (Mexico), Nemko, Fimko, Demko, Semko (Nordic) Eastern European approvals, CE Marking, FCC approval, Energy Star, TCO '99 (emissions, ergonomics, environment), Microsoft® Windows® certified (Microsoft® Windows® 2000 and Microsoft Windows XP), UL listed
Compatibility	Compatible with platforms using VESA standard video modes. Recommended for use with HP products.
Service and Warranty	Limited three years parts, labor, and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. Consult HP Customer Service for details. For details, contact HP Customer Support.

© Copyright 2005 Hewlett-Packard Development Company, L.P.

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided as is without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.